Christie CP4325-RGB

Digital cinema Screening rooms Post production

RealLaser illumination. Unmatched cinematic performance.

The Christie[®] CP4325-RGB pure laser cinema projector brings a premium movie-going experience to mainstream theatres. Featuring CineLife[™] electronics and RealLaser[™] illumination, this compact, all-in-one DCI-compliant projector excels in image quality and operational lifetime while providing a low cost of ownership. With the CP4325-RGB, exhibitors can impress audiences with incredibly colorful and detailed, true-to-life images while benefiting from an affordable platform that will perform well into the future.

RealLaser. Real smart.

What sets Christie RealLaser apart? We've taken everything we know from being the preeminent manufacturer of RGB pure laser projectors and coupled it with the latest innovations in laser devices. The result is an incredibly efficient and long-lasting light source that drastically out-performs any other cinema illumination platform. The long, stable operational life of RealLaser powered projectors means they provide the lowest cost of ownership of any cinema projector in their class. Make bringing the art of exhibition to the next level a reality.



Specifications		Christie CP4325-RGB
Brightness	nominal	• Up to 23,000 lumens (<25°C ambient) ¹
	lifetime	 >30,000 hours to 80% brightness (<25°C ambient)
Contrast ratio		• Up to 6000:1 ²
Digital micromirro device	r	 1.38" Enhanced 4K 3-chip DMD DLP Cinema® 4096 x 2160 (4K)
Color gamut	native gamut	• >90% Rec 2020 coverage
Processing electronics		 Christie[®] CineLife[™] Series-3 (Series-2 IMB compatible - specific models)³ HDMI v1.4a x2 • 16-channel AES (RJ45 x2) 2K120 / 4K48 fps (w/Christie IMB-S3) • Up to 4K120 upgradable Built-in automation controller • 3D Sync Connector (12V 1A powered)⁴
Lens mount configuration		 Fully motorized Intelligent Lens System (ILS™)
Lenses		• 1.25-1.83:1 ¹ • 1.45-2.05:1 ¹ • 1.6-2.4:1 ¹ • 1.8-3.0:1 ¹ • 2.15-3.6:1 • 3.0-4.3:1 • 4.3-6.0:1 • 5.5-8.5:1
Input line voltage		Single phase 220V
Power input requirements		 Input A: 200-240 VAC @ 50-60Hz, 17A, 3300W (11,260 BTU/hr) Input B (UPS input): 100-240 VAC @ 50/60Hz, 10A, 1000W
Cooling		Liquid pressurized/TEC, self-contained • Heat extraction optional
Laser class		Class 1 - Risk Group 3
Dimensions (w/o lens)	size	• (LxWxH): 37.2 x 28 x 21.8" (944 x 711 x 553mm)
	weight	• 285lbs (130kg)
Accessories		 Christie IMB-S3 (153-100102-01) • NAS-S3 8TB storage (153-101103-01) Rack mount pedestal (108-416102-01) Extraction duct adaptor (163-102104-01) Rack mount pedestal adaptor (163-101103-01)

¹ With existing high brightness cinema lens

² With new UHC lens suite


³ Series-2 IMB model compatibility subject to change. Currently supports Dolby IMS3000, GDC SX3000 / SX4000


⁴ Supports all conventional 3D systems except "color separation" based 3D (i.e. 6P)

Key features:


- Long-lasting, high-performance light source - Christie RealLaser illumination provides amazing color, extended contrast capabilities and over 30,000 hours of optimal brightness performance
- The pinnacle of image quality -Expansive color gamut and contrast ratios up to 6,000:1 deliver unmatched presentation quality
- Christie CineLife electronics -Streamlined UX-designed interface for simple playback, scheduling and management of cinema content


- Future-proofed High Frame Rate capable: 4K 48fps or 2K 120fps performance out-of-the-box with upgrade path for 4K 120fps capabilities
- **Compact form factor** Fits seamlessly into existing booths for easy installation
- Backwards compatibility Compatible with existing accessories including the Christie Rack Mount Pedestal and cinema lenses for additional cost savings
- Fully sealed optics Protection from environmental contaminants to maintain optimal performance












Corporate offices Worldwide offices

Christie Digital Systems USA, Inc. Republic of South Africa United States (Arizona) ph: 602 943 5700 Australia France ph: +33 (0) 1 41 21 44 04 Cine**Life** ph: +61 (0) 7 3624 4888 ph: +27 11 251 0000 Cypress ph: 714 236 8610 Germany (Cologne) United States (New York) Brazil Singapore Christie Digital Systems Canada Inc. ph: +55 (11) 2548 4753 ph: +49 221 99 512-0 ph: +65 6877 8737 ph: 646 779 2014 Kitchener Germany (Moechengladbach) ph: +49 2161 566200 China (Beijing) ph: +86 10 6561 0240 South Korea ph: +82 2 702 1601 Independent sales ph: 519 744 8005 consultant offices China (Shanghai) India Spain ph: +86 21 6278 7708 ph: +91 (080) 6708 9999 ph: +34 91 633 9990 Italy ph: +39 (0) 2 9902 1161 Columbia Japan United Arab Emirates ph: +57 (318) 447 3179 ph: +81 3 3599 7481 ph: +971 (0) 4 503 6800 Russia ph: +7 (495) 930 8961 ISO 9001 ISO 14001 Eastern Europe ph: +36 (0)1 47 48 138 United Kingdom ph: +44 (0) 118 977 8000 Mexico ph: +52 55 4744 1790



🛞 Copyright 2017 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4592 Nov 17



CHKISTIE®