CP4220/CP4230

Digital cinema projection Color correction/Timing rooms Digital intermediate suites Executive screening rooms Outdoor exhibition Post production

From the leader in digital cinema

As the pioneer of digital projection technology for cinema, with more digital cinema solutions deployed worldwide than any other manufacturer, it's only fitting that we're the first to offer digital cinema solutions based on 4K, Series 2 DLP* technology from Texas Instruments. The newest additions to the Christie* Solaria* Series provide the only solution built with the Christie 4K+4 advantage. Coupled with the Christie IMB, the Christie Solaria Series is the most reliable, cost-effective 4K DLP Cinema* solution available today.

Now available with Christie Previsto High Frame Rate technology

CHKISTIE





Present 3D and alternative content at its best! Use Brilliant3D™ technology for high performance 3D, displaying every pixel as the director intended.

Align pixels perfectly for optimal image quality.

Streamline time consuming maintenance procedures.

Be the brightest and outperform your competition while saving on costs. Only Christie offers the most enhanced 4K experience for the lowest cost of DLP operation.





- 3 Simplest to maintain
- 4 Lowest cost of ownership

Specifications		CP4220	CP4230
Brightness ¹	lamp	• CDXL-20 (003-000598-XX) • CDXL-30 (003-000599-XX) • CDXL-30SD (003-001165-XX)	• CDXL-20 (003-000598-XX) • CDXL-30 (003-000599-XX) • CDXL-45 (003-000600-XX) • CDXL-60 (003-000601-XX)
	nominal	• ~22,000 lumens	• 34,000 lumens
	screen size	• <70' maximum screen size ¹	•>105 ¹
Contrast ratio		•~2100:1 full field on/off	
Digital micromirror device		• 1.4 Enhanced 4K, 3-chip DMD DLP Cinema • 4096 x 2160 pixels	
Input line voltage		Single phase 220V	• 3 phase 208/400V
Number of colors		• 35.2 trillion	
Supported frame rates		• 2D 2K content up to 120 fps, 3D 2K content up to 60 fps/eye ²	
Lenses	zoom	See christiedigital.com	
	optional	• 1.26x Anamorphic Lens 38-809054-XX • Wide Converter Lens 108-281101-XX • Use of the Anamorphic or Wide Converter Lens requires the MALM 108-111102-XX	
Power supply		• 3.3kW low-ripple switch mode lamp power supply	• 7kW low-ripple switch mode lamp power supply
Accessories		 Christie Integrated Media Block (IMB) 108-384107-01 Nema-L6 30A 250V male PWR plug w/1.5m cord 116-102104-01 Power distribution unit 208V/120V 111-277001-01 Variable aperture kits 38-813028-51 Rack mount stand 108-416102-01 Inline 120V duct fan, 600-CFM 700120-074 	 Christie Integrated Media Block (IMB) 108-384107-01 Lamp power supply cable kit 7.5m 127-103105-01 Lamp power supply cable kit 15m 127-103116-01 Lamp power supply cable kit 30m 127-103127-01 Rack mount stand 108-416102-01 Inline 120V duct fan, 600-CFM 700120-074
Weight		• As installed: 256lbs max (116kg)	• As installed: 245lbs max (111kg) • Lamp power supply: 70lbs max (32kg)

¹ Maximum screen size depends upon various factors such as screen gain, lamp age, geometry, etc.

Consult your Christie representative for detailed analysis. Measured at screen center

² To learn more about high frame rates and the next evolution of digital cinema display see

Light Industrial Unit (LIU-17)

Sheikh Mohammed Bin Zayed Road

Christie's High Frame Rate technology overview.

Middle East

Nad Al Shibba

PO Box: 293762

Dubai - U.A.E

Dubai Silicon Oasis

PH: +971 (0) 4 503 6800

United Kingdom

Branch & EMEA

200 Ashville Way

PH: +44 (0) 118 977 8000

Head Office

Wokingham

RG41 2PL

Berkshire, U.K.

ViewPoint



DLP Cinema' Technology 2009 Academy Scientific and Engineering Award for Color Accuracy





Other EMEA offices

Germany Branch Óffice PH: +49 2161 566 200

France Branch Office PH: +33 (0) 1 41 21 44 04

Representative Office

Eastern Europe

PH: +36 (0)1 47 48 138

PH: +27 71 335 8667

For the most current specification information, please visit www.christieemea.com

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specification's are typical. Due to constant research, specifications are subject to change without notice Printed in Canada on recycled paper. 3408 Oct 12

Africa

Unit C3

Northlands Deco Park

New Market Road

Northriding

Johannesburg

Gauteng South Africa

Randburg

2164



Spain

Italy

Russia

Branch Office

PH: +34 91 633 9990

PH: +39 (0) 2 9902 1161

Independent Sales Consultant Office

Independent Sales Consultant Office PH: +7 (495) 930-8961